NISSIN				Co	ompat	ibility	Char	t																																									Las	t update	e: Mar 20	2021		
Canon Cameras																																																						
	EOSR6	EOS 1Dx Mark II	EOS 1 Dx	EOS 1Ds Mark III	EOS 1Ds	EOS 1D Mark IV	EOS 1D Mark III	EOS1D EOS1D Mark II (N)	Mark		EOS 5 Ds -	EOS 5D Mark IV -	EOS 5D Mark II	EOS 5D	EOS 6D Mark II		EOS 7D Mark II	EOS 7D	EOS 80D	EOS 70D	EOS 60D	EOS 50D	EOS 40D	EOS 30D	EOS 20D	EOS 77D (9000D) (Rebel T7i)-	EOS 760D (8000D) (Rebel T6s)	EOS 750D (Kiss X8i) (Rebel T6i)-	EOS 700D (Kiss X7i) (Rebel T5i)	Rebel S	(Kiss	EOS 600D (Kiss X5) (Rebel T3i)	EOS 500D (Kiss X3) (Rebel T1i)	EOS 450D (Kiss X2) (Rebel XSi)	EOS 400D (Kiss Digital X) (Rebel XTI)	EOS 350D (Kiss Digital N) (Rebel XT)	EOS 300D (Kiss Digital) (Rebel X)	EOS 3000D	EOS 2000D/1500D (Kiss X90) (Rebel 17)	EOS 1100D (Kiss X50) (Rebel T)	OD (Kiss F) (Rebel >	PowerShot G1X Mark II	PowerShot G1X	PowerShot G11	PowerShot G7X	PowerShot G7 / G9 / G10	PowerShot G5X	PowerShot G3X	PowerShot SX11S	PowerShot SX10 IS	- i	EOS M5	EOS M3	EOSM
Nissin Model																																									_			· · · ·										
MG80 Pro New	•	• •	•		_   _	•	•		-   -	_	-	• (	• •	_	•	•	•	•	- •	•	•	•	•	-	-	- •	•	•	•	•	•	• •	•	•	-	-	-	•	• •	•	•	0	0	0	0	0	0	0 (		0	0	0	0 (	0
Air 10s Commander	-	• •	•		-   -	•	•	-   -	-   -	_	_	•	• •	-	•	- 1	•	•	- •	•	•	•	•	-	-	- •	•	•	•	•	•	• •	•	•	-	-	-	•	• •	• •	•	0	0	0	0	0	0	0 (		0	0	0	0 (	0
Air 1 Commander	-	• • *2*3	• *2	•	• 0	•	•	O   •	) 1	*2	• *2	● *2*3	•   •	*1	•	•	• *2	•	_ •	•	•	•	•	• *1	*1	•	•	•	•	•	•	•   •	• •	•	*1	• *1	*1	•	•   •	•   •	•	0	0	0	0	0	0	0		0	0	0	0 1	0
Di700 A	•	• •	•	•	0	•	•	0	•	•	•	*3	• •	*1	*3	•	•	•	- *3	•	•	•	•	• *1	*1	• •	•	•	•	•	•	•	•	•	*1	*1	• *1	•	•	•	•	*5*8	0	0	*5*8	0	● *5*8	0 (	0	0	0	0	0 /	0
i60A	•	• •	•		- 0	•	•	0	<u> </u>	•	•	•	• •	*1	•	•	•	•	• •	•	•	•	•	*1	• (	•	•	•	•	•	•	• •	•	•	*1	*1	*1	•	• •	•	•	-	0	0	-	0	-	- (	0	0			*5 *	*5
i600		• •	•		- 0	•	•	0	-	•	•	•	• •		•	•	•	•	- •	•	•	•	•	• a1	• (	•	•	•	•	•	•	• •	•	•	•	•	•	•	• •	•	•	-	0	0	-	0	-	- (	0	0		•	• •	*5
i40	•	• •	•		- 0	•	•	0	•	•	•	• (	• •	•	● *2 *0	•	•	•	_ 0	•	•	•	•	•	• (		•	•	•	•	•	• •	•	•	-1	•	•	•	• •	•	•	0 8580	*5**		•	.500	•	• •	•	8520	•		-	
i400		• •	•		- 0	•	•	0	•	•	•	• (	• •	•	• • • • • • • • • • • • • • • • • • • •	•	•	•	_ 0	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	• •	•	•	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• 5*6*	• 5*6	• • • • • • • • • • • • • • • • • • • •	• •	• •	• • • • • • • • • • • • • • • • • • • •	-5-8	•	•	•	•
MF18	-	• 0	•	• (	• •	•	•	• •	•	_	-	- (	• •	+	0	•	•	•	• 0	•	•	•	•	•	•	• C	•	0	•	•	•	• •	•	•	-1	-1	•	•	• •	•	•	0	0	0	0	0	0	0 (	0	-3*8	0	0	0	0
MG8000 Extreme (discontinued)	0	0 0	•	0 0	0 0	0	•	0	•	•	•	0	• •	•	0	•	•	•	0 0	•	•	•	•	•	•	• 0	•	0	•	•	•	•	• •	•	•	•	•	0	0	• •	•	0	0	0	0	0	0	0 (	0	0	0	0	0	0
Di866 Mark II (discontinued)	0	0 0	•	•	• 0	•	•	0	•	0	•	0	• •	•		•	- 4	•	0 0	•	•	•	•	•	•	• 0	•	0	•	•	•	• •	•	•	•	•	•	0	0	•	•	0	0	0	0	0	0	0 0	0	0	0	0	0	0
Di700 (discontinued)		0 0	•	0 (	0 0	•	•	0		0	0	0	• •	•	0		*4	•	0 0	•	•	•	•	•	• (	• C	•4	0	•	•	•	• •	•	•	•	•	•	0	0		•	0	0	0	0	0	0	0 (	0				0	0
Di600 (fade out model)	0	O *3	• *7	0 (	0 0	•	•	0	•	•	•	*3 :	• •	•1	<b>•</b>	*7	•	•	O *3	•	-	•	•	•1	•	• C	•	0	•		• *6*7	• •	•	-	•1	•	•	0	0	• •	•	0	0	0	0	*5*8	0		*8	*5*8	0	0	0	0

Compatible Model

o incompatible Model

No information available. To be confirmed.

\*1 HSS High speed sync. and second-curtain sync not supported.

- \*2 For using with those Canon camera models, before Binding setting, please set Commander Air 1 to "Mode 2". At the same time, the second curtain sync can not be selected. For details, please refer to Air 1's user manual page8 Appendix1.
- \*3 When using the the first 4 product's serial numbers digits smaller-than the following value: Di600: 68030 20001~ Di700A:67201000001~ Air 1:C67217001~ i40:67281609001~ an error message would appear on camera display when changing "external flash function setting", but the setting is reflected normally. AF assist lamp function on the flash will not work
- \*4 Wireless Slave mode does not support the camera built-in flash as the master function.
- \*5 Since those camera built-in flash have not the master function, they should use a optional master remote unit (e.g. Canon ST-E2) to control wirelessly any slave flash eqipped optical slave recevier.
- \*6 Zoom head operation not supported.
- \*7 The flash charging lamp in the camera viewfinder will not go out.
- \*8 Limited by the camera system function, Flash TTL function will be disabled when camera set to M manual exposure mode.
- \*9 When shooting in continuous mode, flash exposure of TTL mode may become unstable.

## Note

AF-assist lamp is not supported on Mirrorless cameras.

				Nissin	Flashes								Car	on Flas	hes				
	i40 Canon	Di 466 Canon	Di 622 Canon	Di 622 Mark II Canon	Di 600 Canon	Di 700 Canon	Di866 Mark II Canon	MG8000 Canon	220EX	270EX II	320EX	430EX	430EX11	430EX III-RT	250 EX	580 EX	580 EX II	600 EX RT	600 EX 11- RT
Air R Receiver Canon	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Compatible Model

GN Mode. 25-49 GN Mode. 50-65

NISSIN								c	Comp	atibi	lity (	Chart																																						La	st upd	date: Ma	lar 202	<u>?</u> 1	
Nikon Cameras																																																							
	7.2	Z6 II	92	D5 -	D4s	D3 <	D3.k	252	D3	D2Xs	D2Hs	D2H	1 2	DF 0.	-0.00	0100	D800E	D800	D780	D750	D700	D610	D600	D500-	D300s	00000	D200	0100	BZ500 -		D7200	D/100	D5600 -	000000000000000000000000000000000000000	D5500	D5300	D5200	02000	00000	D3400 -	D3300	D3200	D3100	D3000	060	D80	D70/D70s	D90	D50	D40 / D40×	040 / 040A	Coolpix A	Coolpix P7700	Coolpix P5100	Coolpix P5000
Nissin Model				•					·	•	•	•																																											_
MG80 Pro New	•	•	•	•	•	•	•	•	•	0	0	0		•	•	•	•	•	0	•	•	•	•	•	•	•	•		-	-   (	• (	• •	•	•	•	•	•	•	•	-	•	•	•	•	•	-	-	-	-	-   -	- (	0 (	0	0	0
Air 10s Commander	•	•	•	•	•	•	•	•	•	0 (	0 (	0 0	) (	• (	• (	• (	•	•	•	•	•	•	•	•	•	•	•		) -	-   (	• (	• •	•	•	• •	•	• •	•	•	-	•	•	•	•	•	-	-	-	-	-   -	- (	0 (	0	0	0
Air 1 Commander	0	0	0		*2 *:	2	•	•	•	0 (	0 (	0 0	)	• \$	5	•	•	•	0	•	•	•	•	•	•	•	•			•	• (	• •	• -	-	• •	•	• •	•	•	•	•	•	•	•	•	0	0	0	0	) (	) (	0 (	0	0	0
Di700 A	•	•	•	•	•	•	•	•	•	0 (	0 (	0 0	)	• •	• (	•	•	•	•	•	•	•	•	•	•	•	•		-	-   -	• (	• •	• -	-	•	•	• •	•	•	0	•	•	•	•	•	•	•	•	•	•	•	0 (	0	0	0
i60A	•	•	•	•	•	•	•	•	•	0 (	0 (	0 0	) (	• (	•	•	•	•	•	•	•	•	•	•	•	•	•			• (	• (	• •	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	. [	*4 *	*4	0	0
i600	•	•	•	•	•	•	•	•	•	0 (	0 (	0 0	)	• •	• (	•	•	•	•	•	•	•	•	•	•	•	•		-	-   -	• (	• •	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	• [	*4 *	• *4	0	0
i40	•	•	•	•	•	•	•	•	•	0 (	0 (	0 0	)	• •	• (	•	•	•	•	•	•	•	•	•	•	•	•			•	• (	• •	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	• [	*4 *		*4	*4
i400	•	•	•	•	•	•	•	•	•	0 (	0 (	0 0	)	• •	• (	•	•	•	•	•	•	•	•	•	•	•	•		-	-   -	• (	• •	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	• [	*4 *		*4	*4
MF18	0	0	0	•	•	•	•	•	•	0 (	0 (	0 0	)	• •	• •	•	•	•	0	•	•	•	•	•	•	•	•			•	• (	• •	•	•	• •	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	•	0 (	0	0	0
MG8000 Extreme (discontinued)	0	0	0	•	•	•	•	•	•	0 (	0 (	0 0	) (	•	) (	•	•	•	•	•	•	•	•	•	•	•	•				0	• •			•	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	•	0 (	0	0	0
Di866 Mark II (discontinued)	0	0	0	• *3	•	•	•	•	•	•	0	0 0		•	) (	•	•	•	0	•	•	•	•	•	•	•	•			•	• (	• •			•	•	• •	•	•	•	•	•	•	•	•	•	•	•	•	•		0 (	0	0	0
Di700 (discontinued)	0	0	0	0	•	•	•	•	•	0 (	0 (	0 0	) (	• (	) (	• (	•	•	0	•	•	•	•		•	•	•			) (	0	• •			• •	•	• •	•	•	0	•	•	•	•	•	•	•	•	•	•		0 (	0	0	0
Di600 (fade out model)	0	0	0	0	• •	•	•	•	•	• (	0 (	0 0	) (	• (	) (	•	•	•	0	•	•	•	•		•	, (	•		) (	) (	0 (	• (		) (	• (	•	• (	•	•	•	•	•	•	•	•	•	•	•	•	•		0 (	0	0	0

Compatible Model
 Incompatible Model

No information available. To be confirmed.

\*1 Extremely underexposure (about -2EV) appear when Air 1 mounted on D5 to control wirelessly the slave flash and the flash light does not hit the subject directly, such as bouncing or diffusing,

\*2 In D4 · D4s, when manual flash is set, when you shoot continuously and rapidly manually in the Q mode · 1 sheet shooting mode, emission may be missing. Please understand that it is based on specifications.

\*3 At the time of FP flash, it may be underexposed by about 1 stage compared with the genuine strobe

\*4 SD Mode not supported

\*5 Commander / Flash unit may be freeze when camera turn on the electronic shutter mode with mirror up mode. If Commander / Flash unit freezes, remove and re-insert the battery. Turn off the in-compatible function of camera then power on Commander / Flash unit again.

\*6 A firmware update may required in the future.

AF-assist lamp is not supported on Mirrorless cameras.

				Nissin	Flashes						Nil	con Flas	hes		
	i40 Nikon	Di466 Nikon	Di600 Nikon	Di622 Mark II Nikon	Di700 Nikon	Di866 Nikon	Di866 Mark II Nikon	MG8000 Nikon	00S-8S	009-8S	SB-700	SB-800	SB-900	SB-910	SB-5000
Air R Receiver Nikon	•	•	•	*5	•	•	•	•	•	•	•	•	•	•	•

Compatible Model

Air R's GN Mode. 25-49

Air R's GN Mode. 50-65

\*5 FP/HSS high speed sync function not supported

NISSIN									Com	patik	bility	Char	t																																	Las	updat	e: Mar 2	2021	
Sony Cameras																																																		
	- 60	α7S Mark II	α7S	α7R Mark IV -	α7R Mark III	α7R Mark II	α7R -	α7 Mark III -	α7 Mark II	α7	α6500 -	α6400 -	α6300	α6000	α3000	NEX-7	α99 Mark II -	5	α77 Mark II		α65	a58	α57	α55V	α33	ωθ00	α850	α700	α580	α560	α550	α500	α450	0390	0350	a330	α300	0290	α230	α200	α100	RX1R Mark II -	RX1	RX10	RX10 Mark II	RX10 Mark III -	RX10 Mark IV -	RX100 Mark II	HX400V -	ИХ60V
Nissin Model																																																		
MG80 Pro New	_	_	•	•	•	•	-	•	•	•	-	•	•	•	0	-   -	- *4	•	•   •	•   -	*1	-	*1	0	0	*1	*1	0	0	-	0	0	0	-   (			)   -	0	0	0	0	-	•	•	-	•	•	0	-	•
Air 10s Commander	•	_	•	•	•	•	-	•	•	•	-	•	•	•	0		- *4		•	-	- • *1	_	*1	0	0	• *1	*1	0	0	-	0	0	0	- (		0	) –	0	0	0	0	-	•	•	_	•	•	0	-	•
Air 1 Commander	*4	*4	•	0	*4	*4	•	*4	• *4	•	● *4	-	•	•	0	• (	*4	•	*	1 *]	*1	•	*1	0	0	• *1	• *1	0	0	0	0	0	0	0 0	) (	0	0	0	0	0	0	•	•	•	•	•	•	0	-	•
Di700 A	•	•	•	•	•	•	•	•	•	•	•	-	•	•	• '	• (	•	•	•		•	•	*1	*1	*1	*1	*1	• *1	• *1	0		• *1	• *1	0	•	•	0	*1	*1	*1	*1	•	•	•	•	•	•	•	•	•
i60A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	• '	• (	•	•	•	*	*1	•	*1	*1	*1	• *1	• *1	• *1	• *1	0		• *1	•	0	1 *1		0	*1		*1	*1	*2	•	•	-	•	•	•	•	•
i600	•	•	•	•	•	•	•	•	•	•	•	-	•	•	• '	• (	•	•	•	•	•	•	*1	*1	*1	*1	*1	•	*1	0			• (	0			0	*1	*1	*1	*1	*2	•	•	-	•	•	•	•	•
i40	•	•	•	•	•	•	•	•	•	•	•	-	•	•	• '	• •	•	•	•	*1	*1	•	*1	*1	*1	• *1	• *1	• *1	• *1	0		• *1	• *1	0	1 *1	1 *1	0	*1		*1	*1	*2	•	•	•	•	•	•	•	•
i400	•	•	•	•	•	•	•	•	•	•	•	-	•	•	• '	• *1	•	•	•	*1	*1	•	*1	*1	*1	• *1	• *1	• *1	• *1	0			• *1	0 \$	1 *1		0	*1		*1	*1	*2	•	•	•	•	•	•	•	•
MF18	_	_	•	•	•	•	Ī	•	•	•	-	-	•	•	*3	*1	• -	•	•	*1	*1	•	*1	• *1 *3	*1 *3	• *1	• *1	0	0	0	0	0	0	0 (		0	0	0	0	0	0	*2	•	•	•	•	•	0	•	•

o incompatible Model

No information available. To be confirmed.

\*1 Use the Sony Shoe Adaptor (ADP-AMA)

Use the Sony Shoe Adaptor (ADP-AMA)

\*2 It slightly interferes (contacts) with the EVF. Since you can not use EVF, it can not be used because diopter correction does not work by interfering.

\*3 Optical wireless function are not available.

\*4 For using with those Sony camera models, not support the Air R's HSS High-speed sync function :: α9, α7R Mark III, α7R Mark III, α7 Mark III, α8 Mark III, α8 Mark III, α9 Mark III, α8 Mark III, α8

1. AF-assist lamp is not supported on Mirrorless cameras.

		Nis	sin Flas	hes		So	ny Flash	nes	
		i40 Sony	Di622 Mak II Sony	Di866 Mak II Sony	HVL-F32M	HVL-F42AM	HVL-F43M	HVL-F58AM	HVL-F60M
Air R Receiv	ver Sony *3	•	*2	*2	•	*2	•	*2	•

• Compatible Model

GN Mode. 25-49

GN Mode. 50-65 \*1 Use the Sony Shoe Adaptor (ADP-AMA)

\*2 Use the Sony Shoe Adaptor (ADP-MAA). Due to the design of the ADP-MAA adapter, bad contact may always occur when using ADP-MAA. Depends on the situtaion of use, the operation may be unstable.

\*3 For using with those Sony camera models, the HSS High-speed sync function of the flash inserted on Air R can not be used,  $\alpha$ 9,  $\alpha$ 7R Mark III,  $\alpha$ 7R Mark II,  $\alpha$ 7 Mark III,  $\alpha$ 7 Mark III,  $\alpha$ 7 Mark III,  $\alpha$ 99 Mark II ,  $\alpha$ 6500

NISSIN							Con	npati	bilit	y Cha	art											Last u	pdate:	Mar 20	021	
Olympus Micro Four Thirds / Four T	hirds Ca	meras																								
	E-M1 Mark II (OMD)	E-M1 (OMD)	E-M5 Mark II (OMD)	E-M5 (OMD)	E-M10 Mark III (OMD)	E-M10 Mark II (OMD)	E-M10 (OMD)	PEN-F	E-P5	E-P3	E-P2	E-P1	E-PL8 New	E-PL7	E-PL6	E-PL5	E-PL3	E-PL2	E-PL1	E-PM2	E-PM1	E-620	E-520	E-500	E-410	E-30
Nissin Model	•																						-	•		
Air 10s Commander New (Four Thirds ver.)	•	•	•	•	•	-	•	-	•	•	•	•	•	-	•	•	-	•	•	•	•	_	_	-	-	-
Air 1 Commander (Four Thirds ver.)	•	•	•	•	0	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Di700 A (Four Thirds ver.)	•	•	*3	•	0	•	•	• *1	•	•	•	•	•	•	•	•	•	•	•	•	•	*2	*2	*2	*2	*2
i60A (Four Thirds ver.)	•	•	*1	•	0	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	*2	*2	*2	*2	*2
i600 (Four Thirds ver.)	•	•	*1	•	0	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	*2	*2	*2	*2	*2
i40 (Four Thirds ver.)	*1	•	• *1	•	*4	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	*2	*2	*2	*2	*2
i400 (Four Thirds ver.)	*1	•	• *1	•	*4	•	•	• *1	•	•	•	•	•	•	•	•	•	•	•	•	•	*2	*2	*2	*2	*2
Di466 (Four Thirds ver.)	-	•	0	•	-	0	•	0	•	•	•	•	_	0	•	•	•	•	•	•	•	•	•	•	•	•

Compatible Model
 Incompatible Model
 No information available. To be confirmed.

\*1 Unstable operation may appear when turn on the S-OVF Function ( Optical view finder simulation ) of EVF and shoot with EVF.

 $^{*2} \quad \text{Flash's optical slave wireless mode is incompatible with camera's wireless flash system}.$ 

\*3 Di700A for FT version will be supporting Olympus E-M5 Mark II after flash firmware updated.

\*4 Hardware compatible on or above the following Serial Number: i40: 8A18XXXXXXX~ i400:8927XXXXXXXX~

AF-assist lamp is not supported on Mirrorless cameras.

NISSIN						Con	npati	bilit	y Cha	art											Last u	pdate:	Mar 20	021	
Panasonic Micro Four Thirds Came	eras *4																								
	GH5	GH4	СH3	GH2	GH1	GX8	GX7	GX7 Mark II / GX85 / GX80	GX1	G10	69	G8/G80/G85	67/670	99	G5	63	G2	61	GF2	GF1	LX100	LX7	LX5	LX3	FZ200
Nissin Model																									
Air 10s Commander New (Four Thirds ver.)	•	_	•	_	•	_	•	_	-	_	•	_	_	•	_	-	•	•	•	•	_	•	•	•	•
Air 1 Commander (Four Thirds ver.)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Di700 A (Four Thirds ver.)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
i60A (Four Thirds ver.)	•	-	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
i600 (Four Thirds ver.)	•	_	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
40 (Four Thirds ver.)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
400 (Four Thirds ver.)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Di466 (Four Thirds ver.)	_	•	•	•	•	0	•	0	•	•	-	-	0	•	•	•	•	•	•	•	•	•	•	•	•

Compatible Model
 Incompatible Model
 No information available. To be confirmed.

Note
1. AF-assist lamp is not supported on Mirrorless cameras.

r 2021
E-410
2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2
2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2 *2
FZ200
• •
•
•

<sup>\*4</sup> According to the specifications of Panasonic Lumix series, the continuous shooting function cannot be used when an external flash is installed on the hot shoe.

NISSIN										Con	npati	bilit	y Cha	art													Last u	pdate:	Mar 20	021	
Fujifilm Cameras																															
	GFX 50s	X-H1	X-T4	X-T3	X-T2	X-T1 / X-T1 GS	X-T20	X-T10	X-Pro2	X-Pro1	х-Ез	X-E2S	X-E2	X-E1	X-M1	X-A5	X-A3	X-A2	X-A1	X100F	X100T	X100S	X100	X70	X30	X20	X10	X-S1	HS50EXR	HS30EXR	HS20EXR
Nissin Model																													=	=	
Air 10s Commander	_	•	•	•	*1	*1	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-
Air 1 Commander	*1 *2	•	•	•	*1	*1	•	•	*1	•	•	•	•	•	•	0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	0
Di700 A	*1 *2	•	•	•	*1	*1	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	0
i60A	*1 *2	•	•	•	*1	*1	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	0
i600	*1 *2	•	•	•	*1	*1	•	•	*1	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	0
i40	• *1 *2	•	•	•	*1	*1	•	•	*1	•	•	•	•	•	•	0	0	•	•	•	•	•	•	•	•	•	•	•	•	•	0
i400	*1 *2	•	•	•	*1	*1	•	•	*1	•	•	•	•	•	•	0	0	•	•	•	•	•	•	•	•	•	•	•	•	•	0

Compatible Model

Incompatible Model

This camera supports HSS/FP High speed synchronize function.

\*1 The Fujifilm camera is supporting of High speed synchronize function after camera firmware updated

\*2 Flash can be insert on the hot shoe of main body or that of EVF. When inserted a flash on the EVF shoe, do not tilt-up EVF since this may make the EVF damage.

Note

1. AF-assist lamp is not supported on Mirrorless cameras.

